

2/COR/0002

**CARACTERÍSTICAS GENERALES**

- 20A - 4400W.
- Corte instantáneo por alta tensión.
- Corte retardado por baja tensión (7 segundos).
- Controlado a relé.
- Reconexión automática.
- Supresor de transitorios de línea.
- 3 indicadores luminosos para el estado de funcionamiento.

**CARACTERÍSTICAS GERAIS**

- 20A - 4400W.
- Corte instantâneo em alta tensão.
- Corte retardado em baixa tensão (7 segundos).
- Relé controlado.
- Reconexão automática.
- Supressor transiente de linha.
- 3 indicadores luminosos para o Status Operacional.

**GENERAL FEATURES**

- 20A - 4400W.
- Instant high-voltage cutting.
- Delayed low-voltage cutting (7 seconds).
- Relay controlled.
- Automatic reconnection.
- Line transient suppressor.
- 3 light indicators for the Operating Status.

Minimun dimensions (mm)	125x80x55
Output voltage	180 - 242 Vca
Power	4,4 KVA / 2,2 KVA inductive
Minimal response time	50 mseg
Reconnection delay	2 min
Frequencies	50/60 Hz

**STANDARD VERSION**

**NOTAS - ANOTAÇÕES - NOTES**


---



---



---



---



---



---

**DIBUJO - DESENHO - DRAW**
